

HIGH PERFORMANCE UTM & NEXT-GENERATION FIREWALL



NETWORK SECURITY I ENDPOINT SECURITY I DATA SECURITY

Stormshield SN2000

THE SECURITY SOLUTION IDEAL FOR BUSINESSES & LARGE CORPORATIONS REQUIRING HIGH PERFORMANCE AND FLEXIBILITY.



DON'T CHOOSE BETWEEN PERFORMANCE AND SECURITY

With throughput that can reach 30 Gbps, look no further for better value and performance in a network protection appliance.



TAKE ADVANTAGE OF THROUGHPUT FROM NEW-GENERATION NETWORKS

The SN2000's 10GB fiber network connectivity and unrivalled modularity make it easy to integrate naturally into new-generation networks to meet or anticipate your needs.



UP THE BANDWIDTH OF YOUR NETWORK LINKS

Thanks to their physical link aggregation feature (LACP), Stormshield Network Security appliances ensure greater availability than ever in your infrastructure. By merging several physical interfaces in order to create a single link, you will be able to leverage the bandwidth allocated to this link.



The application control function on Stormshield Network Security appliances makes it possible to curb the use of dangerous applications or those unrelated to work. It is based on a qualitative approach that favors the integration of applications that are truly relevant to corporations and their core business.



BUSINESSES & LARGE CORPORATIONS

Ensure the continuity of your business

All protection technologies needed for responding to the most sophisticated attacks are embedded in the entire range.

Manage vulnerabilities

Obsolete or vulnerable applications on workstations and servers are detected in real time.

Keep your commitments to compliance

Stormshield Network Security products are a key component in ensuring compliance with standards, regulations and norms that require access control (PCI-DSS, ISO 27001 or the Data Protection Act, etc.).

Stay in control of your internet usage

Thanks to advanced filtering and the management of quality of service, you can define the way you want the internet to be used.

.....

echnica specifications

USAGE CONTROL

Firewall/IPS/IDS mode, identity-based firewall, application firewall, Microsoft Services Firewall, detection and control of the use of mobile terminals, application inventory (option), vulnerability detection (option), URL filtering (embedded database or cloud mode), transparent authentication (Active Directory SSO Agent, SSL, SPNEGO), multi-user authentication in cookie mode (Citrix- TSE), global/local security policy.

PROTECTION FROM THREATS

Intrusion prevention, protocol scan, application inspection, protection from denial of service attacks (DoS), protection from SQL injections, protection from Cross-Site Scripting (XSS), protection from malicious Web2.0 code and scripts, Trojan detection, detection of interactive connections (botnets, Command&Control), protection from data evasion, Advanced management of fragmentation, automatic quarantining in the event of an attack, Antispam and antiphishing: reputation-based analysis -heuristic engine, embedded antivirus (HTTP, SMTP, POP3, FTP), detection of unknown malware via sandboxing, SSL decryption and inspection, VoIP protection (SIP), collaborative security: adaptation of the filter policy according to security events or detected vulnerabilities.

CONFIDENTIALITY

Site-to-site or nomad IPSec VPN, remote SSL VPN access in multi-OS tunnel mode (Windows, Android, iOS, etc), SSL VPN agent configurable centrally (Windows), Support for Android/iPhone IPSec VPN.

NETWORK - INTEGRATION

IPv6, NAT, PAT, transparent (bridge)/routed/hybrid modes, dynamic routing (RIP, OSPF, BGP), multi-level internal or external PKI management, internal LDAP directory, explicit proxy, policy-based routing (PBR), QoS management, DHCP client/relau/server, NTP client, DNS proxy-cache, http proxy-cache, high availability, WAN link redundancy, LACP management, Spanning-tree management (RSTP/MSTP).

MANAGEMENT

Web-based management interface, object-oriented security policy, real-time configuration help, firewall rule counter, more than 15 installation wizards, embedded log reporting and analysis tools, interactive and customizable reports, sending to syslog, SNMP v1, v2, v3 agent, automated configuration backup.

Non-contractual document. The features mentioned are those in version 2.1.

* Performance is measured in a laboratory and under conditions ideal for version 2.1. Results may vary according to test conditions and the software version.

** IP size: 60% (48 bytes) - 25% (494 bytes) - 15% (1500 bytes).

PERFORMANCE* 20.6bps Firewall (hnughput (1518 byte UDP) 20.6bps PS throughput - AES128/SHA1 5.6bps PSec throughput - AES256/SHA2 4.6bps Max number of IPSec VPN tunels 5.000 Number of SSL VPN clients (Portal mode) 1.024 Number of simultaneous SSL VPN clients 200 NETWORK CONNECTIVITY 20.000,000 Concurrent connections 2,000,000 Number of interfaces 1.300 (Agg. Dialup, ethernet, loopback, VLAN, ptp,) 1,300 IO/100/1000 interfaces 10-26 10/100/1000 interfaces 0.16 10/100/1000 interfaces 10-26 10/100/1000 interfaces 0.2 8 ports 10/100/1000 - 4 ports 16b Fiber - 4 ports 106b Fiber) 2 SYSIEM 32.768 Max number of static routes 10,240 Max number of static routes 10,240		
Firewall (IMIX**)11 GbpsIPS throughput (1518 byte UDP)20 GbpsIPS throughput (1 Mbyte HTTP Files)12 GbpsAntivits throughput3.2 GbpsVPN*IPS cthroughput - AES128/SHA15 GbpsIPS cthroughput - AES128/SHA24 GbpsMax number of IPSec VPN tunnels5,000Number of SSL VPN clients (Portal mode)1,024Number of simultaneous SSL VPN clients2,000,000Number of instratences2,000,000Number of interfaces1,300(Agg. Dialup, ethernet, loopback, VLAN, pptp,)1,30010/10/1000 interfaces0,16410/2010/1000 interfaces0,22(B ports 10/100/1000 - 4 ports 16b Fiber - 4 ports 106b Fiber)2SYSTEM10,240Max number of filtering rules32,768Max number of dynamic routes10,000Redixing10-19"HaRDWARE10,240Local storage128 GB SSDRacking10-19"Height x Width x Depth (mm)44,5 x 443 x 560Weight8.6 kg (191bs)Packaged Height x Width x Depth (mm)144 x 710 x 573Packaged Height x Width x Depth (mm)200 S05 J 240 S05 J 2		
IPS throughput (1518 byte UDP) 20 6bps IPS throughput 1 Mbyte HTPF files) 12 6bps Antivirus throughput 3.2 6bps VPN* IPS ce throughput - AES128/SHA1 5 6bps IPS ce throughput - AES128/SHA2 4 6bps Max number of IPS ce VPN tunnels 5,000 Number of SSL VPN clients [Portal mode] 1,024 Number of SSL VPN clients 2000 NETWORK CONNECTIVITY 20,000,000 Number of interfaces 2,000,000 Number of interfaces 0,000 Number of interfaces 0,000 Number of interfaces 0,66 106b fiber interfaces 0,66 10700/1000 interfaces 10,60 108b fiber interfaces 0,20 SYSTEM 32,768 Max number of fibering rules 32,768 Max number of static routes 10,200 Rebou	•••••••••••••••••••••••••••••••••••••••	30 Gbps
IPS throughput (1 Mbyte HTTP files) 12 Gbps Antivirus throughput - AES128/SHA1 5 Gbps IPSec throughput - AES128/SHA2 4 Gbps Max number of IPSec VPN tunnels 5,000 Number of SSL VPN clients (Portal mode) 1,024 Number of SSL VPN clients (Portal mode) 2,000,000 NetWORK CONNECTIVITY 2,000,000 Number of main gateways (max)/backup (max) 64/64 Number of interfaces 2,000,000 Number of interfaces 1,030 (Agg, Dialup, ethernet, loopback, VLAN, pptp,) 1,300 CONNECTIVITY 1,300 ID6b fiber interfaces 0-16 100b fiber interfaces 0-16 100b fiber interfaces 0-26 100b fiber interfaces <	Firewall (IMIX**)	11 Gbps
Antivirus throughput - AES128/SHA1 5 Gbps IPSec throughput - AES256/SHA2 4 Gbps IPSec throughput - AES256/SHA2 4 Gbps Max number of IPSec VPN tunnels 5,000 Number of SSL VPN clients (Portal mode) 1,024 Number of SSL VPN clients (Portal mode) 1,024 Number of simultaneous SSL VPN clients 200 Number of simultaneous SSL VPN clients 200,000 Number of interfaces 2,000,000 Number of interfaces 2,000,000 Number of interfaces 2,000,000 Number of interfaces 1,300 IO/100/1000 interfaces 10,266 1056 fibre interfaces 0.165 1050 fibre interfaces 0.168 1050 fibre interfaces 0.26 1050 fibre interfaces 0.26<	IPS throughput (1518 byte UDP)	20 Gbps
VPN* IPSec throughput - AES128/SHA1 5 Gbps IPSec throughput - AES256/SHA2 4 Gbps Max number of IPSec VPN tunnels 5,000 Number of SSL VPN clients (Portal mode) 1,024 Number of SSL VPN clients (Source VPN tunnels 200 Number of simultaneous SSL VPN clients 200 NetWORK CONNECTIVITY Concurrent connections 2,000,000 Number of main gateways (max/backup (max) 64/64 Number of interfaces 1,300 (Agg. Dialup, ethernet, loopback, VLAN, pptp,) 1,300 CONNECTIVITY Concurrent connections CONNECTIVITY 10/100/1000 interfaces 10-26 10/100/1000 interfaces 10-26 10-26 10/5 fiber interfaces 0-48 0ptional interfaces 2 SYSTEM 32,768 32,768 Max number of dynamic routes 10,240 Max number of static routes 10,240 Max number of dynamic routes 10,240 Max number of static routes 10,240 Max number of dynamic routes 10,240 Max number of static routes 10,240 Max number of dynamic routes 10,040 Max number of	IPS throughput (1 Mbyte HTTP files)	12 Gbps
IPSec throughput - AES128/SHA15 GbpsIPSec throughput - AES256/SHA24 GbpsMax number of IPSec VPN tunnels5,000Number of SSL VPN clients [Portal mode]1,024Number of SSL VPN clients [Portal mode]1,024Number of simultaneous SSL VPN clients200NETWORK CONNECTIVITY2,000,000New sessions per second90,000Number of min gateways (max/backup (max)64/64Number of interfaces10,26[Agg, Dialup, ethernet, loopback, VLAN, ppt,]1,300CONNECTIVITY10/100/1000 interfaces10,26105b fiber interfaces0.16105b fiber interfaces0.46(B ports 10/100/000 - 4 ports 16b Fiber - 4 ports 106b Fiber]2SYSTEMSYSTEMMax number of filtering rules32,768Max number of filtering rules32,768Max number of static routes10,000REUUNDANCY10High Availability (Active/Passive)~HaRDWARE10,573Local storage128 GB SSDRacking10 - 19Packaged Height x Width x Depth (nm)184 x 710 x 573Packaged Height X Width X Depth (nm)184 x 710 x 573Packaged Height X Width X Depth (nm)200 CON x 573Packaged Height X Width X Depth (nm)200 CON x 573Packaged Height X Width X Depth (nm)200 CON x 573Packaged Height X Width X Depth (nm)200 CON x 573Packaged Height X Width X Depth (nm)200 CON x 574Packaged Height X Width X Depth (nm)200 CON x	Antivirus throughput	3.2 Gbps
IPSec throughput - AES256/SHA24 6bpsMax number of IPSec VPN tunnels5,000Number of SSL VPN clients (Portal mode)1,024Number of simultaneous SSL VPN clients200NETWORK CONNECTIVITY2,000,000New sessions per second90,000Number of ning gateways (max)/backup (max)64/64Number of interfaces1,300(Agg, Dialup, ethernet, loopback, VLAN, pptp,)1,300CONNECTIVITY10/100/1000 interfaces10/100/1000 interfaces0-16105b fiber interfaces0-80ptional interfaces0-8SYSTEM2Max number of filtering rules32,768Max number of static routes10,000REDUNDANCY1High Availability (Active/Passive)~HARDWARE128 GB SSDRacking10.19"Height X Width x Depth (mm)144.5 x43 x 560Power supply (AC)110-230V 60-50Hz 3.5.15APower consumption230V 50Hz 124W 0.95AFan3Operational temperature5" to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature5" to 40°C (41° to 104°F)Relative humidity, storage (without condensation)20% to 90% @ 40°C	VPN*	
Max number of IPSec VPN tunnels5,000Number of SSL VPN clients (Portal mode)1,024Number of simultaneous SSL VPN clients200NETWORK CONNECTIVITY2,000,000New sessions per second90,000Number of main gateways (max)/backup (max)64/64Number of interfaces1,300(Agg, Dialup, ethernet, loopback, VLAN, pptp,)1,300CONNECTIVITY10/100/1000 interfaces10/100/1000 interfaces0.1610/010/1000 interfaces0.1610/010/1000 interfaces0.8Optional interfaces0.8Qptional interfaces0.8SYSTEM32,768Max number of filtering rules32,768Max number of static routes10,000REDUNDANCY10,000High Availability (Active/Passive)~HARDWARE10,000Local storage128 GB SSDRacking10.19°Height x Width x Depth (mm)144.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power consumption230V 50Hz 3.5.1.5APower consumption230V 50Hz 124'' 0.04''Fan3Operational temperature5" to 40°C (41* to 104*F)Relative humidity, operating (without20% to 90% @ 40°CStorage temperature5" to 40°C (41* to 104*F)Relative humidity, operating (without20% to 90% @ 40°CStorage temperature6" to 40°C (41* to 104*F) <td< td=""><td>IPSec throughput - AES128/SHA1</td><td>5 Gbps</td></td<>	IPSec throughput - AES128/SHA1	5 Gbps
Number of SLL VPN clients [Portal mode]1,024Number of simultaneous SSL VPN clients200NETWORK CONNECTIVITY2,000,000New sessions per second90,000Number of main gateways (max)/backup (max)64/64Number of interfaces [Agg, Dialup, ethernet, loopback, VLAN, pptp,]1,300CONNECTIVITY10/100/1000 interfaces10-26105 fiber interfaces0.16106 fiber interfaces0.16106 fiber interfaces0.210/100/1000 - 4 ports 16b Fiber - 4 ports 106b Fiber]22 SYSTEM32,768Max number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCYImage Static routesHigh Availability (Active/Passive)Image Static routesHeight x Width x Depth (mm)144.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight1.5.6 kg (34.4 lbs)Power consumption230V 50Hz 3.5.1.5APower consumption230V 50Hz 3.5.1.5APower consumption230V 50Hz 3.5.1.5APower consumption230V 50Hz 124W 0.95AFan3Operational temperature5* to 40°C (41* to 104*F)Relative humidity, operating (without20* to 90% @40°CCondensation]20% to 90% @40°CStorage temperature-30* to 65°C (-22* to 149*F)Relative humidity, storage (without5% to 95% @60°C	IPSec throughput - AES256/SHA2	4 Gbps
Number of simultaneous SSL VPN clients200NETWORK CONNECTIVITYConcurrent connections2,000,000New sessions per second90,000Number of main gateways (max)/backup (max)64/64Number of interfaces1,300[Agg, Dialup, ethernet, loopback, VLAN, pptp,)1,300CONNECTIVITY10/100/1000 interfaces10/100/1000 interfaces0-16106b fiber interfaces0-16106b fiber interfaces0-380ptional interfaces0-380ptional interfaces0-381000/1000-4 ports 16b Fiber - 4 ports 106b Fiber)2SYSTEM32,768Max number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCY128 GB SSDHacking110-19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg [19 lbs]Packaged Height x Width x Depth (mm)110-230V 60-50Hz 3.51.54Power consumption230V 50Hz 124W 0.554Fan3Operational temperature5" to 40°C (44" to 104"F)Relative humidity, operating (without20% to 90% e4.0°CCondensation)20% to 90% e4.0°CStorage temperature-30° to 55°C (-22" to 149"F)Relative humidity, storage (without5% to 95% e4.0°C	Max number of IPSec VPN tunnels	5,000
NETWORK CONNECTIVITYConcurrent connections2,000,000New sessions per second90,000Number of main gateways (max)/backup (max)64/64Number of interfaces1,300(Agg, Dialup, ethernet, loopback, VLAN, pptp,)1,300CONNECTIVITY10/100/1000 interfaces10-26106 fiber interfaces0.16106b fiber interfaces0.8Optional interfaces0.8Optional interfaces0.8SYSTEM2Max number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDWARE128 GB SSDLocal storage128 GB SSDRacking10.19°HARDWARE8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)144.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged weight15.6 kg (34.4 lbs)Power consumption230V SDH2 124W 035AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20° to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without condensation)5% to 95% @ 60°C	Number of SSL VPN clients (Portal mode)	1,024
Concurrent connections2,000,000New sessions per second90,000Number of main gateways (max)/backup (max)64/64Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)1,300CONNECTIVITY10/100/1000 interfaces10-26106b fiber interfaces0.16106b fiber interfaces0.8Optional interfaces0.8Optional interfaces0.8SYSTEM2Max number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCY2HaROWARE128 GB SSDLocal storage128 GB SSDRacking10.191Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (191 bs)Packaged Height x Width x Depth (mm)110-230V 60-50Hz 351.5APower consumption230V SDHz 124W 015AFan33Operational temperature5" to 40°C (44" to 104"F]Relative humidity, operating (without condensation)-30" to 65°C (-22" to 149"F]	Number of simultaneous SSL VPN clients	200
New sessions per second90,000Number of main gateways (max)/backup (max)64/64Number of interfaces1,300(Agg, Dialup, ethernet, loopback, VLAN, pptp,)1,300CONNECTIVITY10/100/1000 interfaces10-26105b fiber interfaces0-16105b fiber interfaces0-16105b fiber interfaces0-8Optional interfaces0-8(B ports 10/100/1000 - 4 ports 16b Fiber - 4 ports 106b Fiber)2SYSTEM32,768Max number of filtering rules32,768Max number of static routes10,200REDUNDANCY100000High Availability (Active/Passive)High Availability (Active/Passive)Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)110-230V 60-50Hz 3.5.1.5APower supply (AC)110-230V 60-50Hz 3.5.1.5APower supply (AC)110-230V 60-50Hz 3.5.1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5* to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature.30° to 65°C (-22° to 149°F)Relative humidity, storage (without condensation)5% to 95% @ 60°C	NETWORK CONNECTIVITY	
Number of main gateways (max)/backup (max)64/64Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)1,300CONNECTIVITY10/100/1000 interfaces10-2610b fiber interfaces0.1610Cb fiber interfaces0.98Optional interfaces0.98(By ports 10/100/1000 - 4 ports 1Gb Fiber - 4 ports 10Gb Fiber)2SYSTEM32,768Max number of filtering rules32,768Max number of static routes10,000REDUNDANCY10,000High Availability (Active/Passive)<	Concurrent connections	2,000,000
Number of interfaces1,300(Agg, Dialup, ethernet, loopback, VLAN, pptp,)1,300CONNECTIVITY10/100/1000 interfaces10-26106b fiber interfaces0.161016b fiber interfaces0.161016b fiber interfaces0.8Optional interfaces0.8SYSTEM2Max number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCYVHigh Availability (Active/Passive)VHaRDWARE128 GB SSDLocal storage128 GB SSDRacking10.19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg [19 lbs]Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs]Power consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without condensation)20% to 90% @ 40°C	New sessions per second	90,000
Number of interfaces1,300(Agg, Dialup, ethernet, loopback, VLAN, pptp,)1,300CONNECTIVITY10/100/1000 interfaces10-26106b fiber interfaces0.161016b fiber interfaces0.161016b fiber interfaces0.8Optional interfaces0.8SYSTEM2Max number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCYVHigh Availability (Active/Passive)VHaRDWARE128 GB SSDLocal storage128 GB SSDRacking10.19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg [19 lbs]Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs]Power consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without condensation)20% to 90% @ 40°C	······	
[Agg, Dialup, ethernet, loopback, VLAN, pptp,] 1,300 CONNECTIVITY 10/100/1000 interfaces 10-26 10b fiber interfaces 0-16 100b fiber interfaces 0-16 0ptional interfaces 0-8 0ptional interfaces 0-8 0ptional interfaces 0-8 SYSTEM 2 Max number of filtering rules 32,768 Max number of dynamic routes 10,240 Max number of dynamic routes 10,000 REDUNDANCY ✓ High Availability (Active/Passive) ✓ Hacking 10.19° Hacking 10.19° Height x Width x Depth (mm) 44.5 x 443 x 560 Weight 8.6 kg (19 lbs) Packaged Height x Width x Depth (mm) 184 x 710 x 573 Packaged weight 15.6 kg (34.4 lbs) Power consumption 230V 50Hz 174W 0.95A Fan 3 Operational temperature 5° to 40°C (41° to 104°F) Relative humidity, operating (without condensation) 20% to 90% @ 40°C Storage temperature -30° t		
10/100/1000 interfaces10-261Gb fiber interfaces0-1610Gb fiber interfaces0-80ptional interfaces2(8 ports 10/100/1000 - 4 ports 1Gb Fiber - 4 ports 10Gb Fiber)2SYSTEM32,768Max number of filtering rules32,768Max number of static routes10,000Max number of dynamic routes10,000REDUNDANCY10,000High Availability (Active/Passive)~HaRDWARE28 GB SSDLocal storage128 GB SSDRacking10 - 19°Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C		1,300
1Gb fiber interfaces0-1610Gb fiber interfaces0-80ptional interfaces2(8 ports 10/100/1000 - 4 ports 1Gb Fiber - 4 ports 10Gb Fiber)2SYSTEM32,768Max number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCY10,000HARDWARE2Local storage128 GB SSDRacking10 - 19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power consumption230V 50Hz 1.74W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C	CONNECTIVITY	
10Gb fiber interfaces0-8Optional interfaces2(8 ports 10/100/1000 - 4 ports 1Gb Fiber - 4 ports 10Gb Fiber)2SYSTEMMax number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCY10,000HaRDWARE✓Local storage128 GB SSDRacking10 - 19°Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5.1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without S% tn 95% @ 60°C	10/100/1000 interfaces	10-26
Optional interfaces [8 ports 10/100/1000 - 4 ports 16b Fiber - 4 ports 10Gb Fiber]2SYSTEMMax number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCYVHigh Availability (Active/Passive)VHARDWARE128 GB SSDLocal storage128 GB SSDRacking10 - 19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5" to 40°C (41" to 104"F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22" to 149"F)Relative humidity, storage (without5% tn 95% @ 60°C	1Gb fiber interfaces	0-16
(8 ports 10/100/1000 - 4 ports 16b Fiber - 4 ports 106b Fiber)2SYSTEMMax number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCY10,000High Availability (Active/Passive)✓HARDWARE128 GB SSDLocal storage128 GB SSDRacking10 - 19°Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged Weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5 1.5APower consumption230V S0Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without 5% to 95% @ 60°C	10Gb fiber interfaces	0-8
Max number of filtering rules32,768Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCY10,000High Availability (Active/Passive)✓HARDWARE128 GB SSDLocal storage128 GB SSDRacking1U-19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5.1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without S% to 95% @ 60°C		2
Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCY10,000High Availability (Active/Passive)✓HARDWARE128 GB SSDLocal storage128 GB SSDRacking10 - 19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without 5% to 95% @ 60°C	SYSTEM	
Max number of static routes10,240Max number of dynamic routes10,000REDUNDANCY10,000High Availability (Active/Passive)✓HARDWARE128 GB SSDLocal storage128 GB SSDRacking10 - 19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without 5% to 95% @ 60°C	Max number of filtering rules	32,768
Max number of dynamic routes10,000REDUNDANCYHigh Availability (Active/Passive)HARDWARELocal storage128 GB SSDRacking10 - 19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C [-22° to 149°F]Relative humidity, storage (without5% to 95% @ 60°C		10,240
REDUNDANCY High Availability (Active/Passive) HARDWARE Local storage 128 GB SSD Racking 1U - 19" Height x Width x Depth (mm) 44.5 x 443 x 560 Weight 8.6 kg (19 lbs) Packaged Height x Width x Depth (mm) 184 x 710 x 573 Packaged weight 15.6 kg (34.4 lbs) Power supply (AC) 110-230V 60-50Hz 3.5-1.5A Power consumption 230V 50Hz 174W 0.95A Fan 3 Operational temperature 5° to 40°C (41° to 104°F) Relative humidity, operating (without condensation) 20% to 90% @ 40°C Storage temperature -30° to 65°C (-22° to 149°F) Relative humidity, storage (without 5% to 95% @ 60°C	Max number of dynamic routes	10,000
HARDWARELocal storage128 GB SSDRacking1U - 19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C	REDUNDANCY	
Local storage128 GB SSDRacking1U-19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C	High Availability (Active/Passive)	~
Racking1U - 19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C		
Racking1U - 19"Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C	Local storage	128 GB SSD
Height x Width x Depth (mm)44.5 x 443 x 560Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C		•••••••••••••••••••••••••••••••••••••••
Weight8.6 kg (19 lbs)Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C		
Packaged Height x Width x Depth (mm)184 x 710 x 573Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C		••••
Packaged weight15.6 kg (34.4 lbs)Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C		•••••
Power supply (AC)110-230V 60-50Hz 3.5-1.5APower consumption230V 50Hz 174W 0.95AFan3Operational temperature5° to 40°C (41° to 104°F)Relative humidity, operating (without condensation)20% to 90% @ 40°CStorage temperature-30° to 65°C (-22° to 149°F)Relative humidity, storage (without5% to 95% @ 60°C		•••
Power consumption 230V 50Hz 174W 0.95A Fan 3 Operational temperature 5° to 40°C (41° to 104°F) Relative humidity, operating (without condensation) 20% to 90% @ 40°C Storage temperature -30° to 65°C (-22° to 149°F) Relative humidity, storage (without 5% to 95% @ 60°C		•••••••••••••••••••••••••••••••••••••••
Fan 3 Operational temperature 5° to 40°C (41° to 104°F) Relative humidity, operating (without condensation) 20% to 90% @ 40°C Storage temperature -30° to 65°C (-22° to 149°F) Relative humidity, storage (without 5% to 95% @ 60°C		••••
Operational temperature 5° to 40°C (41° to 104°F) Relative humidity, operating (without condensation) 20% to 90% @ 40°C Storage temperature -30° to 65°C (-22° to 149°F) Relative humidity, storage (without 5% to 95% @ 60°C	· · · · · · · · · · · · · · · · · · ·	
Relative humidity, operating (without condensation) 20% to 90% @ 40°C Storage temperature -30° to 65°C (-22° to 149°F) Relative humidity, storage (without 5% to 95% @ 60°C		
condensation) 20% t0 90% @ 40 C Storage temperature -30° to 65°C (-22° to 149°F) Relative humidity, storage (without 5% to 95% @ 60°C		ט 40 נ (41 ° 10 104 °F) כ יוט 40 נ
Storage temperature -30° to 65°C (-22° to 149°F) Relative humidity, storage (without 5% to 95% @ 60°C		20% to 90% @ 40°C
Relative humidity, storage (without 5% to 95% @ 60°C	-	-30° to 65°C (-22° to 149°F)
		5% to 95% @ 60°L
CERTIFICATIONS	CERTIFICATIONS	
Compliance CE/FCC		

For security with high added value



STORMSHIELD NETWORK VULNERABILITY MANAGER*

Arm yourself with a simple and powerful vulnerability detection tool that leaves no impact on your information system.

Vulnerability Management

Based on data passing through the appliance, Stormshield Network Vulnerability Manager makes an inventory of operating systems, applications used and their vulnerabilities. As soon as a vulnerability appears on your network, you will be kept informed.

Remediation

Stormshield Network Vulnerability Manager offers a set of dedicated reports as well as a real-time dashboard that allow you to stay in control of your deployment.



STORMSHIELD NETWORK EXTENDED WEB CONTROL*

Monitor how users surf the internet on your corporate network and optimize your bandwidth consumption by deploying an effective and high-performance URL filtering solution.

Prevention of web-based threats

Extended Web Control analyzes illions of requests in order to continuously evaluate the risk level of various websites and to block infected or malicious sites from being visited as soon as they are detected.

Advanced filtering for all

The Extended Web Control solution can be enabled on the entire range of Stormshield Network Security products. You can therefore benefit from an advanced filter solution regardless of the size of your company.

KASPERSKY ANTIVIRUS*

Protect yourself by getting equipped with the best antivirus protection solution.

Protection from threats

The Kaspersky antivirus solution on Stormshield Network Security appliances is not based merely on a system of malware signatures, but also integrates emulation mechanisms to identify malicious code proactively.

Peripheral protection

Applying an antivirus inspection on the traffic of all devices connected to the network and relying on a behavioral analysis technology similar to sandboxing, it allows the detection of even unknown attacks.

* Option



Phone +33 9 69 32 96 29

WWW.STORMSHIELD.EU